



INTERFACES Compiere MFG + SCM <-> ERP

Compiere Manufacturing and Supply Chain Management

Open Source Initiative

March 16th, 2005

ERP Interfaces proposal

Version 0.1a

For Public Use

JIT System Software • Research and Development Unit
666 Fifth Avenue New York 10103 • [U.S.A.](#)



INTERFACES Compiere MFG + SCM <-> ERP

Revision	Description
05/05/03	Begin For restricted use
01/09/04	0.0a
03/16/05	0.1a For Public use

© 2003-2005 André Legendre

Compiere is a registered trademark of ComPiere, Inc. Copyright © 1999-2004 ComPiere, Inc. All other brand and product names may be trademarks of their respective companies.

Information presented in this guide is subject to change without notice and does not represent a commitment on the part of André Legendre. All rights reserved.



INTERFACES Compiere MFG + SCM <-> ERP

INTRODUCTION

This document describes a very first proposition for interfaces between ERP and Compiere MFG + SCM.

PRINCIPLE

FILES EXCHANGE PRINCIPLE

Compiere MFG + SCM server sends or gets data to and from ERP using a specialized plugin. These transactions are done in an asynchronous way. These transfers can be done in files inside directories of ERP server using ftp or in messages or directly in database or any similar way.

The data format and the transport layer can be customized in the ERP interface plugin.

INTERFACES STRUCTURE

REQUISITION ORDERS SEND (NOT NEED FOR ERP)

Compiere MFG + SCM record	Send Requisition Orders
Name	REQ+dayNum+hour (hhmmss)
Site	/ERP/MFG_SCM46
Structure	Object or ASCII separated data

Description	Fields	Format	
Kit code or Door Code		Char(15)	
Installation code		Char(10)	
Document code		Char(4)	
Quantity to made		Float	
Date asked		Date	
Message Identification		Char(1)	7 if synchronous message 0 if country 1 if retouching 2 if rotation 5 if offline order 6 if offline order without billing



INTERFACES Compiere MFG + SCM <-> ERP

RECEIPT OF MANUFACTURING ORDERRS (NOT NEED FOR ERP)

Erp record	
Name	REQ+dayNum+hour (hhmmss)
Site according to the manufacturing line	ERP/MFG_SCMXX where XX is the manufacturing line name
Structure	Object or ASCII separated data

Description	Fields	Format	
Manufacturing order		Char(10)	
Installation code		Char(10)	
Document code		Char(4)	
Identifying message		Char(1)	7 if synchronous message 0 if country 1 if retouching 2 if rotation 5 if offline order 6 if offline order without billing
Kit code		Char(15)	
Product code		Char(15)	
Description of the manufactured article		Char(33)	
Family		Char(10)	Depend on production line
Quantity		Float	1
Date asked		Date	HHMMSS
Code composing used		Char(15)	
Quantity used		Float	
Operation number to which is used this component		Char(5)	

In the case of an O.F. of retouching, only the components not used are transmitted to Compiere MFG + SCM.



INTERFACES Compiere MFG + SCM <-> ERP

RECEIPT OF THE COMPONENTS

Compiere MFG + SCM record	
Name	Recep+date+hour
Site	/ERP/MFG_SCM10
Structure	Object or ASCII separated data

Description	Fields	Format	
Order number		Char(10)	
Product code		Char(15)	
Received quantity		Integer	
Supplier delivery note		Char(10)	
Receipt date		Date	DDMMAA
Hour of receipt		Char(6)	HHMMSS
Labels number		Char(15)	
Batch number			



INTERFACES Compiere MFG + SCM <-> ERP

CONSUMPTION OF COMPONENTS

Consumption of components parts sends information about components consumption and fabrication order info. Fabrication order is created in Compiere MFG + SCM automatically from requisition order and manually by offline creation order process. The flag Mflag.ford give information about the type of order. (See chapter 3.1). This enable to manage customer returns, service parts process and rotation.

Compiere MFG + SCM record	
Name	Consump15+date+hour
Site	/ERP/MFG_SCM15
Structure	Object or ASCII separated data

Description	Format	value	Transferred by Compiere MFG + SCM
For every line of components			
Manufacturing order	Char(10)		Yes
Component code	Char(15)		Yes
Component quantity used	Float		Yes
Label's serial number	Char(15)		Yes
Motive rubbish	Char(15)	VALID so good OTHER if rubbish	Yes
Operator code	Char(10)		Yes
Time of station (date and hour)	Date		Yes
Operation number	Char(5)		Yes
Product code	Char(15)		Yes
Kit code	Char(15)		Yes
Installation order	Char(10)		Yes
Flag	Char(2)		Yes
Document code	Char(10)		Yes



INTERFACES Compiere MFG + SCM <-> ERP

EXPEDITION

ERP record	
Name	Exp00+date+hour
Site	/ERP/MFG_SCM00
Structure	Object or ASCII separated data

Description	Format	Value	Transferred by Compiere MFG + SCM	Tables ERP
A line by product (OF)				
Manufacturer order	Char(10)		Yes	
Installation order	Char(10)		Yes	



INTERFACES Compiere MFG + SCM <-> ERP

BOM (PROPOSITION FOR ERP)

Record	
Name	BOM
Site	/ERP/MFG_SCM00C
Structure	Object or ASCII separated data

Description	Fields	Format	
Kit code		Char(15)	
Product code		Char(15)	
Description of the manufactured article		Char(33)	
Family		Char(10)	Depend on Production Line
For each operation			
Operation number to which is used this component		Char(5)	
For each component of each operation			
Code composing used		Char(15)	
Quantity used		Float	



INTERFACES Compiere MFG + SCM <-> ERP

END-ITEMS REJECTS AND CUSTOMER RETURNS

ERP record	
Name	PU10+dayNum+hour (hhmmss)
Site	/ERP/MFG_SCM00A
Structure	Object or ASCII separated data

Description	Fields	Format	
Manufacturing order		Char(10)	

Customer's returns are managed in the same manner than en-items rejects : Scan of a reject label then scans of the Product label. Erp then make a movement between end-items and reject tables. If the product has to be replaced, create an off line order in Compiere MFG + SCM. (see chapter 3.1).

COMPONENTS

ERP record	
Name	Comp+dayNum+hour (hhmmss)
Site	/ERP/MFG_SCM00B
Structure	Object or ASCII separated data

Description	Fields	Format	
Component code		Char(15)	Yes
Description of the component		Char(33)	
workstation		Char(15)	
Short Description		Char(15)	

Component list enable reception to control which components are allowed to go in the plant. Description (and short Description) can be useful for users information. They can be sent directly to users or throw PLC's. The workstation ID is useful when components associates to one workstation have to be sent to several different workstations.